

Disco Dad 321 Manual



File Name: Disco Dad 321 Manual.pdf

Size: 1290 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 25 May 2019, 20:37 PM

Rating: 4.6/5 from 571 votes.

Status: AVAILABLE

Last checked: 6 Minutes ago!

In order to read or download Disco Dad 321 Manual ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Disco Dad 321 Manual . To get started finding Disco Dad 321 Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Disco Dad 321 Manual

KerfAid Dicing Saw Surfactant can be mixed into the DI water to help control issues related to water resistivity, surface tension, viscosity and pH control. Discover everything Scribd has to offer, including books and audiobooks from major publishers. Start Free Trial Cancel anytime. Report this Document Download Now Save Save Disco 321 For Later 100% 1 100% found this document useful 1 vote 578 views 418 pages Disco 321 Uploaded by Tuan Anh Nguyen Description Full description Save Save Disco 321 For Later 100% 100% found this document useful, Mark this document as useful 0% 0% found this document not useful, Mark this document as not useful Embed Share Print Download Now Jump to Page You are on page 1 of 418 Search inside document Browse Books Site Directory Site Language English Change Language English Change Language. Substrates to 6 inch diameter and 3 mm in thickness, mounted on dicing tape held on a thin sheet metal frame. The Australian Government through ARENA is supporting Australian research and development in solar photovoltaic and solar thermal technologies as part of its commitment to making renewable energy technologies more affordable and increasing the amount of renewable energy used in Australia. The views expressed herein are not necessarily the views of the Australian Government, and the Australian Government does not accept responsibility for any information or advice contained herein. Please use one of these links to upgrade to a modern web browser Firefox, Google Chrome, Internet Explorer. Researchers wishing to use the facilities are required to review the new and additional safety material listed in the link at the left side of this page. Let us know how we can improve your experience. It is also possible to provide these services with machines that are not shown here. And processing with some equipment can be conducted in a clean room. For details, please contact your DISCO sales representative. <http://www.kk-gorenjska.si/uporabnik/file/candy-ci-5140-xt-manual.xml>

- **disco dad321 manual, 1.0, disco dad321 manual.**

It is also possible to provide these services with machines that are not shown here. For details, please contact your DISCO sales representative. Please read here for details regarding the handling of personal information at DISCO. Well cared for by major manufacturer. They advised that the saw was in good operational. This saw was one of many being used by a major international. Flocked shirt 13. flocking drying cleaning. adhesive. application. creation User's Guide Step Two Import your DXF file in FlowPATH Advanced Circuits Inc 2004 Prefire Before Using. Spalling. Kiln Shelf Youth Handouts BrightLink Pro Features. 1 Turning on and Calibrating the Projector Installation Instructions A SpaceClaim Support Document The substrates can be bare, with thin films or without, patterned or etched. Turn on high heat. 2. Mount the substrate silicon wafer or piece to be diced in the center of the correct metal frame. 1 Turn on the substrate vacuum. Place it as close to the center as possible. b. The correct frame is placed around the substrate. The larger the air bubbles the less likely the pieces will stay stuck to the tape once cut. f. Close the top and spin to cut the tape around the frame. g. Raise the top, turn off the substrate vacuum, and remove mounted substrate and frame. 3. Turn on the Disco Dicing saw by turning the key to START until the green light comes on. Let go of the key and let it return to ON. Just like starting a car. The screen will remain dark for a while. 4. Once the screen comes on it will read Initialize System at the bottom left. Press the SYS INIT button. The system will then initialize and once done will read G007 Initialization complete 5. Blade Setup a. Go to the Blade Maintenance menu F5 b. Enter the Blade Setup menu F3 c. Start the Non Contact Setup F3 d. When the bottom left of the screen reads G074 Press the ENTER key to execute press ENTER 2. <http://ahkjt.com/upfile/candy-condenser-tumble-dryer-manual.xml>

The vacuum gauge should move from red to green, if it does not you will need to adjust your dicing frame and substrate until it does. 7. Select Device Data F4 to choose a program. Scroll up and down and press ENTER when the one you wish to use is highlighted. Any program may be chosen and modified. 8. Using the up and down scroll through and change the program to suit your substrate or piece. Press F8 to enter the measure view and see the substrate through the lenses. 13. Press EXIT once to return to the commands at the bottom of the screen. 3 Use the SLOW key to make finer movements. The INDEX key will move the substrate the distance set in the program. 15. Choose a line that runs across the width of the substrate or two features that are even. Using the movement keys, align to the three dashed lines across the screen. 4 The cut is made between the three lines on the screen. To increase accuracy place the first cut at the end of the substrate closest to you. 17. Choose the cut direction F5 if you are at the front of the substrate F10 if you are at the back of the substrate 18. Select START to start the cut. 19. The program may ask to verify the jog direction of the movement keys. Perform the verification by briefly touching the specified underlined key. 20. Reselect the cut direction and press START. 21. When the cuts are finished, dry off the substrate using the nitrogen gun. Should they not be available, please contact any staff member for assistance.

6. APPROVAL QUALIFIED TRAINER TRAINING COORDINATOR Jolene Chorzempa Stephanie Bozic 5. It is equipped with a CCD camera and a 5" monitor. In addition there is a wafer spinrinsedryer tool that makes sure that the diced components are clean and dry after the dicing. The wafer can be cut into dice of any size and angles. Downloaded data may be viewed as often as you like. The variety of instruction manuals models and types will be increased in the future for customers who use and carefully maintain old equipment models.

Instruction manuals for the latest major models can be downloaded here .If your company' s main store or office is located in Japan, the consumption tax 10% will be applied. Or a nonJapanese person who works for a Japanese company Development, manufacturing, use, and storage of the followings. Weight 2,425. Mod. Precision Dicing Saw Multi axis cutting, X travel 11.5 inche. Equipment Name 2226. Configuration. Year June, 1998. Saw Two sample mounting presses in one. Model 16744. Description. Series 401 Dicing Wheel. Condition. New Never. Diamond Sc. Model 13741. New Never Used Version 300 mm X axis. Useable stroke 220 mm. Bearing type A. X axis. Useable stroke Max 160 mm. Application Cutting for 6 inch. X axis. Useable stroke. Equipment Automatic Dicing Saw. Status Excellent Without builtin UV. In very good working condition. For Sale or Lease with CS. Wafer Size 300mm. Touch Screen Display with GUI interfa. Users perform workpiece loading, alignment, and unloading manually. Substrates up to 6" diameter and 3 mm in thickness are mounted on dicing tape which has a sticky backing that holds the wafer on a thin sheet metal frame. The dicing machine runs at high power 2.4KW, which makes this instrument capable of cutting hard and thick materials like bonded wafers up to 8 inches. Return to full instrument list. Features. Non Contact Setup Microscope With Eyepiece and Shutter. Broken Blade Detection. Floppy Drive. Includes. Light Tower. B. Mesa, AZ, USA Click to Request Price Disco DAD 321 Manufacturer Disco Disco Dicing saw Trim, Ireland Click to Request Price 2002 Disco DAD 321 96991 Manufacturer Disco Wafer Dicing Saw. Fully operational with major preventative maintenance completed. Full config attached Light tower. Includes blade removal tools. Yes No Please tell us more so that we can improve our website How can we get in touch with you optional Send Feedback Thank you for making Machinio better. Your feedback is greatly appreciated.

<https://ayurvedia.ch/boss-dr-groove-202-manual>

Operation of the dicing saw is through a touchscreen LCD, through which the user supplies a recipe for cutting, performs manual alignments, and processes the wafer in an automatic or semiautomatic cutting sequence. Workpiece loading and unloading is done manually at the front of the machine. The DAD 3240 can handle small pieces as well as 4", 6", or 8" inch wafers that are mounted on dicing tape. Other materials with consent of lab staff. If necessary, samples should be cleaned in

solvents, followed by DI rinse and N2 blow dry. Particular attention should be paid to the back side of the sample which will be adhered to the dicing tape. If particles from cutting are a potential problem, a coating i.e. photoresist or similar may be applied prior to cutting. The LCD touch panel allows for easy operation and displays alarm history and realtime temperature data. Our organization's goal is to provide your company with upmost quality service and support. We recognize each customer's individual needs and provide service upon their requirements. Our team prides itself on honesty, dependability and respect. We have over 20 years of experience in the semiconductor industry. When you purchase used dicing saws from Semiconductor Systems, you are getting top quality equipment at a competitive rate. Well assume youre ok with this, but you can optout if you wish. Ce site Web utilise des cookies pour ameliorer votre experience. Nous supposons que cela vous convient, mais vous pouvez vous desinscrire si vous le souhaitez. Out of these cookies, the cookies that are categorized as necessary are stored on your browser as they are essential for the working of basic functionalities of the website. We also use thirdparty cookies that help us analyze and understand how you use this website. These cookies will be stored in your browser only with your consent. You also have the option to optout of these cookies.

<http://www.niarads.com/images/Dinon-Manual-244X244.pdf>

But opting out of some of these cookies may have an effect on your browsing experience. This category only includes cookies that ensures basic functionalities and security features of the website. These cookies do not store any personal information. It is mandatory to procure user consent prior to running these cookies on your website. Note Missing viewer lights Super high amount of views. 0 sold, 1 available. More Super high amount of views. 0 sold, 1 available. You are the light of the world. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Austin Healey Sprite Repair Manual. To get started finding Austin Healey Sprite Repair Manual, you are right to find our website which has a comprehensive collection of manuals listed. Our library is the biggest of these that have literally hundreds of thousands of different products represented. I get my most wanted eBook Many thanks If there is a survey it only takes 5 minutes, try any survey which works for you. Inc Technical Services Depanment 3030 Laura Lane Middletori. WI 53562 Lunes a Viernes. 800 AM a 600 PM Hora Estdndar del Centro 80017754382 6081831,4116 Europa ETC Europe Ltd. Technical Services Department 5 Victoria Industrial Estate Victoria Road. London W3 6UU Asia ETC Asia. Por ejemplo. si un canal esta incluido tanto en un submaster como en una preparacion que se ha corrido v esta en un atenuador. Azul En Tracksheet y Blind solamente. Esquina de teclado Modo de visualizacion numerico Visualizacidn del nivel de los canales Area de informacidn e indicaciones para el usuario Barra de atributos Teclas de funcion Modo de visualizacidn El modo de visualizacidn y la hora actuales Esquina de teclado numerico Indica como interpretara la consola el siguiente numero entrado desde el teclado numerico Por ejernplo. Visualizacion del nivel de los canales El nivel actual de los canales en la preparacibn. Todos los demas elementos de la pantalla permanecen sin cambio.

<http://ladylordwest.com/images/Dinstar-8-Port-User-Manual.pdf>

La unica diferencia de trabajar con el Flexichannel activo estd en la seleccidn de canales. Ver Seleccionando canales en el modo Flexichannel en la pagina 53 para mayor infor. macidn. Nora En los modos Tracksneety Patch los canales aparecen resalrados si esrari en la hsrar del Flexichannel. SI no estdn en la Itsta. Actualizando el flexichannel Cuando los cariales que fueron utilizados en un show son removidos del show. Purge Flexi. para actualizar las visualizaciones del Flexichannel. Ventana de Parcheo Erilista los canales. Gran maestro Nombre del show Lista de Subrnasters Lista de Preparaciones Status de los atenuadores Gran maestro Establecimiento actual del Grandmaster y la alerra de Blackout Apagado instantaneo de luces Nombre del sho w Nombre del 5show cargado actualmente en la consola Lista de Submasters Pagina de Submaster y Lista de Submasters La lista incluye submasters. We are a nonprofit group that run this service to share

documents. We need your help to maintainance and improve this website. Dicing tape has different properties depending on the dicing application. UV curable tapes are used for smaller sizes and nonUV dicing tape for larger die sizes. Once a wafer has been diced, the die will stay on the dicing tape until they are extracted. The Disco DAD 3220 is a single spindle dicing saw which can take up to 6" of substrates. Standard blades are suitable for cutting silicon. Other blades are also available upon request. Registration is quick and easy and will give you full access to the site and allow you to ask questions or make comments and join in on the conversation. If you would like to register then please [Click Here](#) For a better experience, please enable JavaScript in your browser before proceeding. It may not display this or other websites correctly. You should upgrade or use an alternative browser. OK so my Disco 3 is 5 years old. But what a rubbish design. Cant they get this thing right on the Disco.

Its also fitted on the new 4 and I hear, on some Jags as well. The problem seems to be that the thing seizes up. It might start with a few little warning messages on the dash or maybe an intermittent flashing orange light with the letter P in a circle. The next thing you know, youre starting the engine and theres a hellish screech coming from the back end. The car wont move as the handbrake is seized on and youre stuck. When my first one went it was out of warranty and cost me a few hundred quid for a new one. Lucky that I keep all my receipts and so when it went again I could prove it was less than 12 months old and didnt have to pay. But really, what a poor design. I mean, why fit these things if they are clearly such a problem. The guy who recovered my vehicle confirmed that they are frequently called out to recover Discos and Jags with this EPB module fault. bout time someone sorted it or we go back to a normal handbrake perhaps When you say there are warning messages, are these right before it seizes or do you have a bit of a warning its about to go. Anyone know if theres been any updates to the latest model If you need to emergency release the handbrake.you simply need to read the owners manual and it will tell you how. You say its happened 3 times since the warrenty has run out.thatll be 3 times in 2 years if the first time you had to pay for it. It sounds like poor maintaince. It will of properly been out of adjusted and the first time you heard the squeeling noise, could of stripped cleaned and adjusted. And for it to happen again twice in 2 years then i would look no further then the garage that fitted the bits in the first place as it sounds like they arent doing something right. If you need to emergency release the handbrake.you simply need to read the owners manual and it will tell you how.

And for it to happen again twice in 2 years then i would look no further then the garage that fitted the bits in the first place as it sounds like they arent doing something right.I had to laugh out loud at it actually I was wondering whether I have to carry a pair of dice with me and throw a double to start. I just checked back on my service bills and I have exaggerated somewhat. In fact, I have had 2 not 3 new EPB modules in 5 years. I have had the car back 3 times though for this fault. The first one went about a year ago I recall it was Easter time and we were up in Northumberland on a small family holiday at the time. I had seen the intermittent flashing orange light with P on it a few days previous. These little warning lights often come and go with no consequence. For example, Ive had warning messages about coolant level being low, about transmission faults, about engine management faults and handbrake faults and none of them, when checked out, have been found to be real. Just a sensor thats a bit hyperactive here or there. If a light comes on and stays on though, thats a different matter and that would force me to act straightaway. But a little flicker. Id just get it checked on the next occasion I go to the garage. So, to answer your question Obzi USUALLY, you get a little warning but on this last occasion the third occasion there was no warning whatsoever. All I know is I was picking my kid up from football training and his dads car was the one that was screeching like a demented banshee and rocking back and forth in its parking spot. I should mention that the 2nd occasion it didnt need an EPB it needed releasing and adjusting. The fact that when I got it home after the second occasion it had a loose metal cable trailing underneath it which meant I had to take it back again probably confirms Cockys supposition that the garage just aint doing it

right. Main dealer strikes once again!

Although it does have its problems for some vehicles as you've clearly demonstrated DerbyTup overall, it works well if the garage knows how to maintain it. Firstly, if you get the screeching noise, then get it adjusted URGENTLY. If you continue to use it and screech, then it WILL break the EPB actuator. Secondly, if your garage CORRECTLY sets up the EPB and adjusts as they should do at each service, then you should not have any problems at all. I have worked on my own D3 and that of others and whilst the correct setup process is sometimes time consuming, it is not mechanically difficult. BUT you DO have to follow the process correctly and fully. Shortcuts when adjusting the EPB will mostly result in failure. I have found that users have downloaded it and even if they don't use it themselves, they've given it to their indies to make sure that they do the job fully and correctly. I can't stress the importance enough of following the correct adjustment procedure. DT, if you had a cable hanging down, then that really does point to incompetence on installation as it's very unlikely to break in that way. In terms of working out how to release a stuck EPB, then you just remove the flap of plastic that sits behind the EPB switch. Look around in there for a hoop of wire should be clear or white plastic covered steel cable and then pull on it with a screwdriver through the hoop. You need something like 220nm of force to release it, so not for the weak. By continuing to use this site, you are consenting to our use of cookies. To read more from Good Weekend magazine, visit our page at The Sydney Morning Herald, The Age and Brisbane Times. I feel much more safe as an actor now. Check below for more deets about Christie Whelan Browne. Plays Scarlett Brady. Have a Good Weekend all week. She has also started to become more strategic about her career.

Loving Captivity a sweet, techsavvy web series about love and dating in quarantine Sony offers first look at romantic comedy Spin Out, starring Xavier Samuel If Whelan Browne sometimes has anxieties about her abilities, there are some very influential people who do not. It's more that I don't just want to be seen as that. Christie Whelan Browne Infertility is not something to be ashamed of By Benjamin Law. We are parsing more detailed wiki about Christie Whelan Browne that we will modernise within 24 to 48 hours. Stage and screen actress Christie Whelan Browne says she does not regret accusing actor Craig McLachlan of assaulting her in 2014. Short Biography. Christie Whelan Browne is one of Australia's most versatile stage and screen performers. Christie Whelan Browne born 6 August 1982 is an Australian actress who has worked extensively in musical theatre. Geoffrey Rush has become a mentor to her after they worked together on the Melbourne Theatre Company musical Im not smart like them, so I would never say that we could be friends because they're geniuses, the two of them, she says. So I kind of realised that's where I need to be. The work kept coming from there, as did the rave reviews. There's too much keeping her here, including two young nieces she adores and looks forward to seeing at the family dinners every Sunday night at her parents house. Growing up in Eltham in a closeknit family that includes older brother Marcus, now a chef, and older sister Kate, a teacher, the Whelan clan was obsessed with basketball, and young Christie wasn't much interested in school. I don't know how a person could be called the names that I've been called and be painted in a way and not be affected. I haven't been able to hold on to that to know who I am, know that I'm a good person. Soundtrack To miss out on things like that, I don't know what kind of job is worth that. Site design by is miriam lass clarice starling. Se voce continuar a navegar o site, voce aceita o uso de cookies.

Leia nosso Contrato do Usuario e nossa Politica de Privacidade. Se voce continuar a utilizar o site, voce aceita o uso de cookies. Leia nossa Politica de Privacidade e nosso Contrato do Usuario para obter mais detalhes. Alem disso, serao aplicados os Termos gerais de uso e a Politica de Privacidade da Scribd. Se prefira sair da plataforma, por favor, encerre sua conta do SlideShare. Saiba mais. Altere suas preferencias de anuncios quando desejar. Compartilhe! Manual do Proprietario. Certificado de Garantia. Moto Honda da Amazonia Ltda. Este manual deve ser considerado como parte permanente do veiculo e deve continuar com o mesmo. Ele contem todas as instrucoes basicas

para que sua HONDA possa ser bem cuidada, da inspecao Sua motocicleta HONDA e uma verdadeira maquina de precisao. E como toda maquina de precisao, Sua Concessionaria HONDA tera satisfacao em ajudalo a manter e conservar sua motocicleta. Ela Aproveitamos a oportunidade para agradecerlhe a escolha de uma HONDA e desejamos que sua Equipamentos de protecao. VIII. Modificacoes. VIII. Opcionais. VIII. Cuidados com alagamentos. VIII. Acessorios. 1. Cargas. 3 Instrumentos e luzes indicadoras. 8 Suspensao. 10. Freios. 11. Embreagem. 15. Combustivel. 17. Verificacao do nivel de oleo do motor. 20. Recomendacoes sobre os pneus. 21. Interruptor de ignicao. 23. Interruptores do guidao direito. 24. Interruptores do guidao esquerdo. 25 Suporte do capacete. 27. Assento. 28. Compartimento para documentos. 29. Tampa lateral. 29 Partida do motor. 31. Conducao da motocicleta. 33. Cuidados para amaciar o motor. 35. Frenagem. 36. Estacionamento. 37. Como prevenir furtos. 38 Acelerador. 53. Bateria. 65. Carburador. 52. Cavalete Lateral. 64. Controle de Revisoes. 42. Corrente de Transmissao. 54. Cuidados na Manutencao. 46. Espelho retrovisor. 64. Filtro de Ar. 47. Identificacao da Motocicleta. 45. Indicador de Desgaste Jogo de Ferramentas. 44. Limpeza de Lonas e Tambor Oleo do Motor. 48. Pastilhas do Freio Dianteiro. 62. Regulagem do Farol. 69.

Remocao e Instalacao Remocao e Instalacao Troca de Fusiveis. 67. Troca de Oleo do Motor. 49. Vela de Ignicao. 51 HONDA. Por isso, se sua motocicleta Gerente de Servicos da concessionaria. Madureira, 1500 CEP 04021001 Sao. Paulo SP Departamento de Servicos . Pos Vendas Setor de atendimento a Pilotar uma motocicleta requer certos cuidados Regras de seguranca Dirija somente O passageiro deve segurarse com as Modificacoes na motocicleta ou a remocao de Opcionais. Dirijase a sua concessionaria autorizada. Honda para obter mais informacoes sobre os Cuidados com alagamentos. Ao trafegar em locais alagados, riachos e A entrada da agua no carter do motor causara CONCESSIONARIA para certificarse da A instalacao de acessorios e carga pode Acessorios. Os acessorios originais HONDA foram Nao instale Toda pane no Alem de afetar A instalacao de tais acessorios submete os A utilizacao de O peso e a acomodacao da carga sao muito Distribua o peso uniformemente dos dois Capacidade. Esta motocicleta foi projetada para transportar Distribuicao de pesos NAO SERAO COBERTOS pela Garantia. HONDA. Se estiver em duvida sobre como Pedal do freio Pedal de apoio Pedal de apoio Bateria Filtro de ar. Pedal de Pedal do Suporte do Pedal de apoio Cavalete Se a inspecao antes do uso pag. 30 nao for A posicao I e recomendada para cargas leves As posicoes II a V aumentam progressivamente Certifique-se de que os dois amortecedores Para ajustar a tensao das molas dos Esta motocicleta possui um freio dianteiro a Dirijase a uma Nivel do fluido do freio Abasteca o reservatorio com fluido Remova os parafusos 2, a tampa do Abasteca o reservatorio com o fluido do freio Outras verificacoes. Certifique-se de que nao ha vazamentos. Verifique se a mangueira e conexoes estao Para regular, gire a Ajustes menores sao obtidos atraves do Solte a contraporca 5 e gire a porca de Certifique-se de que o motor nao apresenta Honda para que seja feita uma inspecao no Outras Verificacoes.

Verifique se ha dobras ou sinais de desgaste O registro de combustivel 1, com tres O registro deve ser O tanque de combustivel tem capacidade Para retirar a tampa do tanque 1, abra a Combustivel recomendado Apos abastecer, recoloque a tampa no bocal A gasolina e extremamente inflamavel e ate Apos abastecer, O nivel de oleo deve ser mantido entre as Ligue o motor e Operar o motor com oleo insuficiente pode Verifique a pressao dos pneus frequentemente Verifique se ha cortes, pregos ou outros Dirijase a uma concessionaria HONDA para Use pneus de mesma medida e do mesmo O uso de outros tipos Pressao dos pneus Somente piloto 175 1,75; 25 200 2,0; 29 Piloto e passageiro 175 1,75; 25 225 2,25; 33 Nao retire ou Profundidade minima dos sulcos Dianteiro 1,5 mm. Traseiro 2,0 mm Posicao da chave Funcao Condicao da chave. LOCK trava da coluna A coluna de direcao e travada. Motor e sistema eletrico A chave pode ser OFF Motor e sistema eletrico desligados A chave pode ser ON Todas as luzes podem ser ligadas. O motor pode ser A chave nao pode ser O interruptor de emergencia 1 esta Na posicao RUN, o motor pode ser ligado. Na Interruptor de partida. Quando o interruptor de partida 2 e Consulte nas paginas 31 e 32 os Interruptor do farol. O interruptor do farol

3 possui duasH Farol, lanterna traseira e lampadas dosPressione o comutador 1 em “Hi” paraInterruptor da luz de passagem. Pressionando o interruptor da luz deInterruptor das sinaleiras. Mova o interruptor das sinaleiras 3 para “L”Pressione o interruptor para desligar asInterruptor da buzina.

Pressione o interruptor da buzina 4 paraPressione a chave de ignicao 1 e virea paraNao gire a chave para a posicao LOCKIntroduza aGire a chave de ignicao no sentido antihorarioO suporte do capacete foi projetado paraPuxe o assentoPara instalar o assento, encaixe a lingueta doPressione a parteO Manual do Proprietario e outros documentosQuando lavar a motocicleta, tenha cuidadoSe a inspecao antes do uso nao for executada,Inspecone sua motocicleta diariamente, antesVerifique se ha vazamentos.Ajuste e lubrifique, se necessario.Corrija qualquer anormalidade antes de dirigirHONDA sempre que nao for possivelNunca ligue o motor em areas fechadas ouSolte o interruptor deDe qualquerOperacoes preliminares. Certifique-se de que a transmissao esteja emPartida com o motor quenteMotor afogado. Se o motor nao funcionar apos variasOFF e mantenha o afogador desacionado. Abra completamente o acelerador e acione oAguarde 10 segundos, coloque o interruptorSe o suporteA coordenacaoNao efetue a mudanca de marchas semCada toque noNao reduza as marchas com o motor em altaO motor podeDurante os primeiros 1000 km, conduza suaEvite aceleracoes bruscas e utilize as marchasAlem de aumentarEvite freadas violentas.Entretanto,Funcionar o motor alem da rotacao maximaAcione a embreagem antes que aUma frenagem extrema pode travar as rodasEvite que criancaA chuva temTrave a coluna de direcao para prevenir furtos.A funcao do tubo de dreno do carburador eAo estacionar aUsualmente o CDI e curtocircuitado e tal recursoMuitas vezes, as motocicletas sao identificadasHonda e quem melhor conhece suaEste programa de manutencao e baseadoManutencao. Sua concessionaria Honda poderaAs motocicletasTanque e tubulacoes Verificar 3.000 —. Filtro de combustivel Limpar 3.000 —. Acelerador Verificar e ajustar 3.000 53. Afogador Verificar e ajustar 3.000 —. Filtro de ar Limpar obs. 2 3.000 47. Vela de ignicao Limpar e ajustar 3.000 51. Trocar 8.000 51. Folga das valvulas Verificar e ajustar 3.000 —.

<https://formations.fondationmironroyer.com/en/node/12237>