



U.S.A. Website: <http://us.lg.com>  
Canadian Website: <http://lg.ca>

### ELECTRIC & GAS DRYER SERVICE MANUAL

**CAUTION**  
READ THIS MANUAL CAREFULLY IN ORDER TO  
PROPERLY DIAGNOSE PROBLEMS AND TO SAFELY  
PROVIDE QUALITY SERVICE ON THESE DRYERS.



DLEY1201\* DLGY1202\*

**File Name:** Dlgy1202V Manual.pdf

**Size:** 4646 KB

**Type:** PDF, ePub, eBook

**Category:** Book

**Uploaded:** 11 May 2019, 20:30 PM

**Rating:** 4.6/5 from 762 votes.

**Status:** AVAILABLE

Last checked: 1 Minutes ago!

**In order to read or download Dlgy1202V Manual  
ebook, you need to create a FREE account.**

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

### Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dlgy1202V Manual . To get started finding Dlgy1202V Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



## Book Descriptions:

# Dlgy1202V Manual

Please enable JavaScript to ensure you get the most out of the LG site, products, and services. In order to get the best possible experience from our website, please follow below instructions. If you're using Internet Explorer 9 or earlier, you will need to use an alternate browser such as Firefox or Chrome or upgrade to a newer version of Internet Explorer IE10 or greater. Please have the Serial number of your product and proof of purchase ready. Out-of-warranty service fees may apply for diagnosis, parts, and labor. This help library content will show you how to clean your tub, dispenser, water inlet filters and the exterior part of your machine. Performing a reset on the washer will not. This content covers both electric and gas dryers. Watch this video to learn about Reasons Why You. We can help. Choose from a range of commercial displays, enterprise mobility solutions and solar modules providing specialised solutions for a range of business types. Find commercial appliances and electronics from LG for your business and help make life good. Whether that means cooking a nutritious, delicious meal for your family, staying connected on the go, sharing your favorite photos, watching a movie with your kids or creating a clean, comfortable place to celebrate the moments that matter, we'll be there for you every step of the way. Designed with you in mind, LG products offer innovative solutions to make life good. With intuitive, responsive controls, sleek, stylish designs, and eco-friendly features, our collection gives you the power to do more at home and on the go. It includes Explore our complete collection of LG electronics, mobile devices, appliances and home entertainment solutions and find everything you need to connect and family, no matter where they are. This will simplify installation and ensure that the dryer is installed correctly and safely. Ask your question here. Provide a clear and comprehensive description of the issue and your question. <http://www.rosettes.co.uk/userfiles/canon-l800-manual.xml>

- **dlgy1202v manual, dlgy1202v manual, dlgy1202v manual.**

The more detail you provide for your issue and question, the easier it will be for other LG Electronics DLGY1202V owners to properly answer your question. Ask a question About the LG Electronics DLGY1202V This manual comes under the category Dryers and has been rated by 1 people with an average of a 7. This manual is available in the following languages English, Spanish. Do you have a question about the LG Electronics DLGY1202V or do you need help. Ask your question here LG Electronics DLGY1202V specifications If the above does not help, a mechanic should be called in. ManualSearcher.com ensures that you will find the manual you are looking for in no time. Our database contains more than 1 million PDF manuals from more than 10,000 brands. Every day we add the latest manuals so that you will always find the product you are looking for. It's very simple just type the brand name and the type of product in the search bar and you can instantly view the manual of your choice online for free. ManualSearcher.com If you continue to use this site we will assume that you are happy with it. Read more Ok. This service and repair manual is used by the Official Certified LG Technicians. It will help you to troubleshoot and repair your dryer. Please note this is the OFFICIAL service and repair manual in PDF format, no scanned or bootlegged copy. This manual is made in the highest resolution, so when you print the pages you need it is all in great quality. INSTANT DOWNLOAD! You will have instant access to your download. No shipping fee, no waiting on postal delivery, you can start doing your repairs right away. Specifications Language English Format PDF Pages 40 By continuing to use this website you are giving consent to cookies being used. Do you know the answer All manuals on ManualsCat.com can be viewed completely free of charge. By using the Select a language button, you can choose the language of the manual you want to view. DrYer. <http://d2005.ru/userfiles/canon-laser-class-3170-fax-machine-manual.xml>

Before beginning installation, read these instructions carefully. this Enforcement Act Electricity Homes For your safety, the information in this manual must be followed to minimize the risk of fire or explosion, electric shock, or to prevent Your Safety and the safety of others is very important. We have provided many important safety messages in this manual and on your appliance. Always read and obey all safety messages. This is the safety alert symbol. This symbol alerts you to potential hazards that can kill or hurt you and others. All safety messages will follow the safety alert symbol and either the word DANGER, WARNING, or CAUTION. These words mean You will be killed or seriously injured if you don't immediately follow instructions. You can be killed or seriously injured if you don't follow instructions. You may be slightly injured or cause damage to the product if you do not follow instructions. All safety messages will tell you what the potential hazard is, tell you how to reduce the chance of injury, and tell you what can happen if Do not install a clothes dryer with flexible plastic venting materials. If flexible metal foil type duct is installed, it must be of Flexible venting materials are These conditions will obstruct clothes dryer airflow and increase the risk of Installation and service must be performed by a qualified installer, service agency, or the gas supplier. Do not use any phone in your building. Follow the gas supplier's instructions carefully. For your safety, the information in this manual must be followed to minimize the risk of fire or explosion, electric shock, or to prevent To reduce the risk of fire, electric shock, or injury to persons when using this appliance, follow basic precautions, including the following. California Safe Drinking WATER and Toxic Enforcement Act.

This act requires the governor of California to publish a list of substances known to the state to cause cancer, birth defects, or other Gas appliances can cause minor exposure to four of these substances, namely benzene, carbon monoxide, formaldehyde, and soot, caused Properly adjusted dryers will minimize incomplete combustion. Exposure to these substances can be minimized further by properly Before use, the dryer must be properly installed as described in Do not place items exposed to cooking oils in your dryer. Items Do not dry articles that have been previously cleaned in, washed Do not reach into the dryer if the drum or any other part is Do not repair or replace any part of the dryer or attempt any Before the dryer is removed from service or discarded, remove the Do not allow children to play on or in the dryer. Close supervision Do not use fabric softeners or products to eliminate static unless Do not use heat to dry articles containing foam rubber or similarly Keep area around the exhaust opening and adjacent surrounding The interior of the dryer and exhaust vent should be cleaned Do not install or store the dryer where it will be exposed to the Do not store plastic, paper, or clothing that may burn or melt For your safety, the information in this manual must be followed to minimize the risk of fire or explosion, electric shock, or to prevent Improper connection of the equipment grounding conductor can result in a risk of electric shock. Check with a qualified electrician or To reduce the risk of fire, electric shock, or injury to persons when using this appliance, follow basic precautions, including the following. Properly ground dryer to conform with all governing codes Electric shock can result if the dryer is not properly grounded.

<http://www.bosport.be/newsletter/boss-me-50-manual-portugues>

Before use, the dryer must be properly installed as described Install and store the dryer where it will not be exposed to All repairs and servicing must be performed by an authorized Failure to follow this To reduce the risk of electric shock, do not install the dryer in Connect to a properly rated, protected, and sized power Improper power circuit can. Remove all packing items and dispose of all shipping Place dryer at least 18 inches above the floor for a garage Keep all packaging from children. Packaging material can be There is a risk of suffocation. Do not install near another source of heat such as a stove, Do not place candles, smoking materials, or other flammables Dripping wax, smoke, or fire can result. Remove all protective vinyl film from the product. Failure to do This appliance must be grounded. In the event of malfunction The plug must be Do not modify the plug provided with the appliance. If it will not fit This appliance must be connected to a grounded metal,

permanent Electric shock can result if the dryer is not properly grounded. For your safety, the information in this manual must be followed to minimize the risk of fire or explosion, electric shock, or to prevent To reduce the risk of injury to persons, follow all industry recommended safety procedures including the use of long sleeved gloves and Gas dryers MUST be exhausted to the outside. Failure to follow The dryer exhaust system must be exhausted to the outside of Use only rigid metal or flexible metal 4 inch diameter Ductwork is not provided with the dryer, and you should The end cap should The exhaust duct must be 4 inches 10.2 cm in diameter with Rigid or semirigid metal ducting is recommended for use In special installations The use of this ducting will affect drying time. Failure to follow DO NOT use sheet metal screws or other fasteners which Secure all joints with duct tape. For complete details, follow the Installation Instructions.

Failure to For your safety, the information in this manual must be followed to minimize the risk of fire or explosion, electric shock, or to prevent To reduce the risk of fire, electric shock, or injury to persons when using this appliance, follow basic precautions, including the following To prevent injury to persons or For personal safety, this dryer must be properly grounded. Failure to do so can result in electric shock or injury. Refer to the installation instructions in this manual for specific Failure to follow these This dryer must be plugged into a properly grounded outlet. Electric shock can result if the dryer is not properly grounded. Have the wall outlet and circuit checked by a qualified Failure to follow these instructions can create an electric shock. The dryer should always be plugged into its own individual Never unplug your dryer by pulling on the power cord. Always Repair or replace immediately all power cords that have Do not use a cord that When installing or moving the dryer, be careful not to pinch, This will prevent injury and An entire selection of userfriendly functions make operating the dryer easy. The door hinge can be reversed to adjust for installation location. Should you experience any technical difficulty with your dryer, it has the capability of transmitting data via your telephone to the. Customer Information Center. The call center agent records the data transmitted from your machine and uses it to analyze the issue, Protocol P154. Sanitization Performance of. Residential Clothes dryer Accessories. Terminal block Control panel. Leveling feet. Reversible Lint filter Gas connection Power cord Exhaust duct Water Inlet. Valve For your safety and for extended product life, use only authorized components. The manufacturer is not responsible for product The images in this owner's manual may be different from the actual components and accessories, and are subject to change by the Optional accessories. Drying rack Side vent kit Included accessories.

Y connector Hose Following are instructions for starting and using your new dryer. Please refer to specific sections of this manual To reduce the risk of fire, electric shock, or injury to persons, read this entire manual, including the Important. Safety Instructions, before operating this dryer. Press to turn the dryer ON. Press again to turn the MANUAL DRY cycles to adjust the drying time. Press the MORE TIME button to increase the selected The current settings are shown Simply select the STEAM AUTO OFF To conserve energy, the dryer shuts off The display shows the settings, estimated time remaining, options, and status messages for your A Estimated Time Remaining. This display shows the estimated time remaining for. SENSOR DRY cycles or the actual time remaining for. TIMED DRY or MANUAL DRY cycles. Maintaining COOLING, or WRINKLE CARE. C Child Lock Indicator. When CHILD LOCK is set, the CHILD LOCK indicator will check FILTER reminder. The display will show CHECK FILTER when the dryer is It turns off Checking and choosing Leveling the dryer. Connecting Electric Dryers Venting the Dryer. Plugging in the power Connecting Gas Dryers Test run Press and hold Read all installation instructions completely before installing and operating your dryer. It is important that you review this entire Detailed instructions concerning electrical connections, gas connections, and exhaust At lower temperatures, the dryer might not shut off at the end of an automatic Some codes limit, or do not permit, installation of the dryer in garages, closets, mobile homes or A level floor with a maximum slope of 1 inch 2.5 cm under entire dryer. If

slope is greater than 1 inch 2.5 cm, install the Extended Dryer. Feet Kit. Clothes may not tumble properly, and automatic sensor cycles may not operate correctly if dryer is not level. For a garage installation, you will need to place the dryer at least 18 inches 46 cm above the floor. If using a pedestal, you will need 18Clearances.

Installation spacing for recessed area or closet installation. The following spacing dimensions are recommended for this dryer. This dryer has been tested for spacing of 0 inches 0 cm clearance onThere should be at least a little space around the dryer or any other appliance to eliminate the transfer of vibration from one to theA location that allows for proper exhaust installation. A gas dryerSee Venting the dryer. A grounded electrical outlet located within 2 ft. 61 cm of eitherA sturdy floor to support the total dryer weight of 200 lbs 90.7No other fuelburning appliance can be installed in the sameAdditional spacing should be considered for ease of installationAdditional clearances might be required for wall, door and floorAdditional spacing should be considered on all sides of the dryerFor closet installation, with a door, minimum ventilation openingsLouvered doorsCompanion appliance spacing should also be considered. Closet Door Vent. Requirements. Requisitos de ventilacionRecommended installation spacing for cabinet installation. For cabinet installation with a door, minimum ventilation openings in the top of the cabinet are required.Leveling the dryerTo reduce the risk of injury to persons, adhere to all industryFailure to follow thisThe appliances are heavy. Two or more people are requiredFailure to follow this warning canTo ensure that the dryer provides optimal drying performance,Position the dryer in the final location. Place a level across theAll four leveling feet must rest solidly on the floor. Gently pushIf you are installing the dryer on the optional pedestal, you mustUse an adjustable wrench to turn the leveling feet. TurnRaise or lower the leveling feet until dryer is level from side toMake sure that all 4 leveling feet are in firm contact with the floor. Level. Leveling FeetRemove the two plastic cover caps.

Reinstall the hingesWith the hinges and cover caps in the new locations, remountTest the swing of the door to make sure the hinges and latch areTo avoid damage to the dryer or the door, support the door with a stoolAvoid dropping the door to avoid damage to the door or the floor.Open the door and remove the two plastic hole caps on theSave these for step 6. While supporting the door, remove the 4 screws, two fromWith the door on a protected surface, remove the 12 screwsRemove the latch hook andReversing the door. Hole cap. Hinge screw. Inner door frame. Latch hook. HingeCover cap. Swing DoorTo reduce the risk of injury to persons, adhere to allFailure to follow all of the safety warnings in this manual couldYour new dryer is shipped to vent to the rear. It can also be configured to vent to the bottom or side rightsideAn adapter kit, part number 383EEL9001B, may be purchasedThis kit contains the necessary ductRemove the rear exhaust duct retaining screw. Pull out theOPTION 1 Side Venting. Press the tabs on the knockout and carefully remove thePress the adapter duct onto thePreassemble a 4 inches 10.2 cm elbow to the next 4inchesSecure in place with duct tape. Be sure that the male end of the duct protrudes 1 inches 3.8Attach cover plate to the back of the dryer with included screw. OPTION 2 Bottom Venting. Press the adapter duct onto the blower housing and secure toInsert the 4 inches 10.2 cm elbow through the rear openingBe sure that the male end ofSecure in place with duct tape. Attach the cover plate to the back of the dryer with includedRear. Exhaust Duct. Retaining. Screw. Elbow. Cover. Plate. Knockout. Bracket. Adapter. Duct. DuctCover. PlateTo reduce the risk of fire, electric shock, or injury to persons when using this appliance, follow basic precautions, including the following. Do not crush or collapse ductwork. Failure to follow theseDo not allow ductwork to rest on or contact sharp objects. Failure to follow these instructions can result in fire or death.

If connecting to existing ductwork, make sure it is suitableFailure to follow theseVenting must conform to local building codes. Failure to followGas dryers MUST exhaust to the outdoors. Use only 4inch 10.2 cm rigid or flexible metal ductworkTo reduce the risk of fire, combustion, or accumulation ofFailure to follow these instructions can result in fire or death. To reduce the risk of

fire, DO NOT exhaust the dryer with Failure to follow these instructions can result in fire or death. The exhaust duct must be 4 inches 10.2 cm in diameter with Rigid or semirigid metal ducting is recommended for use In special installations The use of this ducting will affect drying time. Failure to follow DO NOT use sheet metal screws or other fasteners which Secure all joints with duct To maximize operating results, please observe the duct length Failure to follow these Ductwork is not provided with the dryer. You should obtain The end cap should have The Total length of flexible metal duct shall not exceed 8 ft. In Canada, that only those foil type flexible ducts, if any, In the United States, that only those Outline for Clothes Dryer Transition Duct, Subject 2158A, shall be Deduct 6 ft. 1.8 m for each additional elbow. It is not recommended. Routing and Connecting Ductwork. Follow the guidelines below to maximize drying performance and Ductwork and fittings are NOT included and must be purchased Use 4 inch 10.2 cm diameter rigid or semirigid metal ductwork. The exhaust duct run should be as short as possible. The male end of each section of exhaust duct must point away from Insulate ductwork that runs through unheated areas in order to Incorrect or inadequate exhaust systems are not covered by the Ductwork. Wall Cap Type Maximum Length of Metal Duct Recommended. Use only for short Incorrect Venting. Correct Venting The dryer must be connected to the cold water tap using the new water supply hose. Do not use old hoses Connect the water supply hose to the dryer inlet valve tightly by.

Make sure that there are no kinks in the hoses and that they are Check for leaks at the Y connector if used and all hoses. Check rubber seal in the inlet hose. Two rubber seals are They are used for preventing Hose Y connector Long Connect all water supply hoses tightly by hand and then. When connecting the dryer to the same faucet Connect the short hose to the Y connector using one of the Connect the other end of the short hose to the cold water Connect the long dryer hose to one side of the Y connector and If the dryer does not share the cold water Connect the straight end of the long hose to the cold water faucet. This will help prevent Do not overtighten. Damage to the coupling can result. Rubber seal To reduce the risk of fire, electric shock, or injury to persons when using this appliance, follow basic precautions, including the following. Electrical requirements for gas models only To reduce the risk of fire, electric shock, or injury to persons when using this appliance, follow basic precautions, including the following. Do not, under any circumstances, cut or remove the third Failure to follow this For personal safety, this dryer must be properly grounded. Failure to follow this warning can result in fire, explosion, or death. The power cord of this dryer is equipped with a 3 prong Failure to follow this warning This dryer must be plugged into a 60 Hz, 120 VAC, grounded Where a standard 2 prong wall outlet is encountered, it is your Failure to follow this Gas supply requirements. As shipped from the factory, this dryer is configured for use Propane gas. Gas pressure must not exceed 13 inches of A qualified service or gas company technician must connect Failure to do so can result in fire, explosion, or death. Isolate the dryer from the gas supply system by closing its Supply line requirements. Your laundry room must have a rigid gas supply line to your MUST be installed within at least 6 ft. 1.8 m of the dryer, in Canadian gas installation code CSA B149.1.

A 1 Failure to do so can result in fire, If using a rigid pipe, the rigid pipe should be inch IPS. If acceptable under local codes and ordinances and when Failure to do so can result in fire, explosion, or death. Connect the dryer to the type of gas shown on the nameplate. Failure to do so can result in fire, explosion, or death. To prevent contamination of the gas valve, purge the gas DO NOT use an open flame to inspect for gas leaks. Use a Failure to do so can result in Use only a new AGA or CSA certified gas supply line with Failure to do so can result in Securely tighten all gas connections. Failure to do so can result DO NOT attempt any disassembly of the dryer; any Failure to do so can Use a pipe joint compound that is insoluble in Liquefied. Petroleum LP gas on all pipe threads. Failure to do so can To reduce the risk of fire, electric shock, or injury to persons when Installation and service must be performed by a qualified Failure to do so Use only a new stainless steel flexible connector and a new. AGA certified connector. Failure to do so can result in fire, A gas shutoff valve must be

installed within 6 ft. 1.8 m of The dryer is configured for Natural Gas when shipped from Gas or Liquefied Petroleum. Failure to do so can result in fire, If necessary, the correct orifice for the LP, orifice kit order All connections must be in accordance with local codes and Gas dryers MUST exhaust to the outdoors. Failure to do so can Connecting the gas supply. Make sure that the gas supply to the laundry room is turned. OFF. Confirm that the type of gas available in your laundry room The dryer is prepared for Natural. Gas with a 3 Remove the shipping cap from the gas connection at the back Connect the dryer to your laundry room's gas supply using a Securely tighten all connections between the dryer and your Turn on your laundry room's gas Electrical connection. High altitude installations.

The BTU rating of this dryer is A G certified for elevations below If your gas dryer is being installed at an elevation above 10,000 Plug dryer into a 120 VAC, Connection Gas Supply. Shutoff Valve. Plug. Stainless Steel Flexible. Connector To help prevent fire, electric shock, serious injury, or death, the Electrical requirements for electric models only To reduce the risk of fire, electric shock, or injury to persons when The dryer has its own terminal block that must be connected If branch circuit to dryer is 15 ft. 4.5 m or less in length, Allow sufficient slack in The power cord pigtail connection between wall receptacle Failure to follow A 4 wire connection is required for all mobile and A 4 wire connection must To reduce the risk of fire, electric shock, or injury to persons when Do not modify the plug and internal wire provided with the If it does not fit the outlet, a proper outlet will need to be To reduce the risk of fire, electric shock, or injury to persons when Any installation in a manufactured or mobile home must CSA Z240 MH and local codes and ordinances. A 4 wire connection is required for all mobile and Failure to do so can result USA only Connect the power cord to the terminal block. Connect teach Failure to follow these instructions may result in a short, Grounding through the neutral conductor is prohibited Power cord. A 4 wire connection is required for all mobile and manufactured AWG minimum copper conductor power cord through the Transfer the dryer's ground wire from behind the green ground Attach the two Attach the white neutral wire to the center terminal block Reinstall the terminal ULListed. Strain Relief. ULListed Cord. Terminal. Block. Neutral Hot Hot Power Cord. Ground Wire. Ground. White Wire Ground Screw USA only Connect the power cord to the terminal block. Connect each Failure to follow these instructions may result in a short, Grounding through the neutral conductor is prohibited Four wire connection for electric dryers Direct wire.

A 4 wire connection is required for all mobile and manufactured Remove 5 inches of insulation from the ground wire. Cut off Remove the terminal block access cover on the upper back of Allow at least 5 ft. 1.5 m length to allow for removal and Transfer the dryer's ground wire from behind the green ground Attach the two Attach the white neutral wire to the center terminal block Reinstall the terminal Ground Wire ULListed. Connect each Failure to follow these instructions may result in a short, Grounding through the neutral conductor is prohibited Power cord. A 3 wire connection is NOT permitted on new construction after. January 1, 1996. Remove the terminal block access cover on the upper back of AWG minimum copper conductor power cord through the Attach the two hot leads of the power cord to the outer Attach the neutral wire to the center Connect the external ground if required Tighten a L ULListed. Neutral Hot Hot External Ground. Wire If required White Wire USA only Connect the power cord to the terminal block. Connect each Failure to follow these instructions may result in a short, Grounding through the neutral conductor is prohibited Three wire connection for electric dryers Direct wire. Remove 3 1 Strip 1 inch 2.5 cm insulation from each wire. Bend the ends of Remove the terminal block access cover on the upper back of Allow at least 5 ft. 1.5 m length to allow for removal and Attach the two hot leads of the power cord to the outer Attach the neutral wire to the center Connect the external ground if required Tighten all ULListed. Wire If required White Wire Any installation in a manufactured or mobile home must comply If you are uncertain whether your A gas dryer must be permanently attached to the floor.

The electrical connection for an electric dryer must be a 4-wire. To reduce the risk of combustion and fire, the dryer must be DO NOT vent the dryer under a manufactured home or mobile. Electric dryers may be vented to the outside using the back, left. Gas dryers may be vented to the outside using the back, left. The dryer exhaust duct must be affixed securely to the It is recommended that you use a rigid or flexible metal duct. DO NOT connect the dryer exhaust duct to any other duct, vent. Make sure the dryer has adequate access to outside fresh air to The opening for outside fresh air must Please be aware that venting materials are not supplied with Final installation check. Once you have completed the installation of the dryer and it is Testing dryer heating When the dryer starts, The exhaust air should Checking airflow. Effective dryer operation requires proper airflow. The adequacy of the airflow can be measured by evaluating Static pressure in the exhaust duct should not exceed 0.6 inches Checking levelness. Once the dryer is in its final location, recheck the dryer to be sure If this happens, the igniter Once you have completed the installation of the dryer, use this This test should be performed Your dryer features Flow Sense™ To activate the installation test. Remove the drying rack and literature, and then close the Do not load anything in the drum for this test, as in may affect Press and hold the TEMP. CONTROL and OPTION buttons This button sequence activates the installation test. The code The dryer will start the test, which will last about two minutes. The heat will be turned on and the temperatures in the drum Check the display for results. During the three minute test cycle, monitor the Flow. Sense™ If no bars are displayed, Refer to the next page for error code details and solutions. Four bars indicates that the exhaust system is severely restricted. Have the system checked immediately, as performance will be End of cycle. At the end of the test cycle, will display.

<http://www.diamondsinthemaking.com/content/boss-me-50-manual-portugues>