Dovre 2510 Manual



File Name: Dovre 2510 Manual.pdf

Size: 4072 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 27 May 2019, 12:38 PM **Rating:** 4.6/5 from 706 votes.

Status: AVAILABLE

Last checked: 7 Minutes ago!

In order to read or download Dovre 2510 Manual ebook, you need to create a FREE account.

Download Now!

eBook includes PDF, ePub and Kindle version

- ☐ Register a free 1 month Trial Account.
- ☐ Download as many books as you like (Personal use)
- ☐ Cancel the membership at any time if not satisfied.
- **☐ Join Over 80000 Happy Readers**

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dovre 2510 Manual . To get started finding Dovre 2510 Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Dovre 2510 Manual

Ask your question here. Provide a clear and comprehensive description of the issue and your question. The more detail you provide for your issue and question, the easier it will be for other Dovre 2510 owners to properly answer your question. Ask a question About the Dovre 2510 This manual comes under the category Fireplaces and has been rated by 1 people with an average of a 5.2. This manual is available in the following languages English, Dutch, German, French, Spanish, Italian. Do you have a question about the Dovre 2510 or do you need help. Ask your question here Dovre 2510 specifications ManualSearcher.com ensures that you will find the manual you are looking for in no time. Our database contains more than 1 million PDF manuals from more than 10,000 brands. Every day we add the latest manuals so that you will always find the product you are looking for. Its very simple just type the brand name and the type of product in the search bar and you can instantly view the manual of your choice online for free. ManualSearcher. com If you continue to use this site we will assume that you are happy with it. Read more Ok. De pr ima ir elu chts chu if r e g e lt de lucht on d e r h e t ro o s ter. D e s ecu n d a ir e lu chts chu if r e g e lt de lu cht voorhet glasair wash. Ad vie zen Stook nooit met op en deur. Stook het toes tel r e g e lma tig f lin k do o r. Als u la n g d u r ig o p lag e s t a n d st o o kt, k a n zic h in d e sc h o orsteeneen afzett ing vormen van teeren creo soot. Teeren creo soot zijn zeerb r a n d b a a r. Als de afz e tt in g van de ze st offen te g r o o t w o r d t, k a n bij ee n plo ts e ling e ho g e t e m p e r a tuu r ee n sc h o o r st e e n b r a n d o n ts taa n. D o o r r e g e lma tig f lin k do orstoken, ver dwijne neventue le afzettingenvanteerencreosoo t.http://psiholab.com/royal/userfiles/96-honda-accord-manual-for-sale.xml

 dovre 2510 manual, dovre 2510 manual pdf, dovre 2510 manual download, dovre 2510 manual transmission, dovre 2510 manual instructions, dovre 2100 manual.

Daarnaastkanzich bij telaagstokenteerafzetten op de ruiten de urvan het toe st e l. Bij e e n mild e b u ite n t e mp e r a tu u r is he t du s b e ter o m h e t t o e st e l ee n pa a r uu r in te n s t e la t e n br a n d e n, d a n la n g e tijd la a g te s toke n. R e g e l de luchtt o e voe r met de s ecu n d a ir e lu cht in laa t. D e s ecu n d a ir e lu chtinla a t b e lu c h t n ie t alle e n h e t v u u r ma a r oo k he t g las, z o d a t he t gla s nie t sne l v e r vuilt. Ze t d e p r ima ir e luchtinla a t tij d e lijk op e n als d e lu cht toe voe r v ia d e secu n d a ir e lu chtinla a t o n v o ld o e n d e is of a ls u h e t v u u r wilt a a n w a kk e r e n. R e g e lma tig e e n klein e ho e vee lh e id h o u tb lokk e n bij vulle n is b e t e r da n ve e l h o u tblo kk e n teg e lijk. R e g e lma tig e e n klein e ho e vee lh e id b r u in koo lb r ikett e n o f a n tra cietk o le n toe vo e g e n is be te r d a n vee l b r u inko o lb r ik e tt e n o f a n tra cietk o le n teg e lijk. D oven van het vuur Vul g e e n b r a n d st o f bij e n la a t de k a che l ge woo n uit g a a n. Als ee n v u u r wor d t ge temp e r d do o r de lucht toe voe r t e ver min deren, komen schadelijk estoffen vrij. Laat daar om het vuur van zelfuitbran de n. Hou d toe zicht op het vuurt ot dathet goedisgedoofd. Alshet vuurvolledigis g e d o o fd k u n n e n a lle lu chts chu iven w o r d e n ge sloten. O ntassen N a he t s token v a n h o u t b lijf t e e n r e la tief kl e in e ho e vee lh e id a s o v e r. D it a s b e d is ee n go e d e is ola to r voordestookbodemengeefteenbetereverbranding. Laatdaaromgerustee n du n l a a g je a s op d e s too kbo d e m lig g e n. N a he t s token v a n b r u in koo lb r iketten e n an tra ci e tk o le n b lijft e r r e la tief vee l as o

ver.http://laboratorioshamalab.com/userfiles/96-harley-sportster-manual.xml

Ver wijde r re g e l ma tig de ove r t o llig e a s. D e as ma g n o o it d e o n d e r kan t van he t r o o s ter r a ken. H e t r o o s ter ra a kt da n over ver h it en b e sc ha d igd. D e l u c h t t o evoe r d oo r d e s took b od em magechternietworden belemmerden er magzich geen as ophopen a chter ee n b in n e n p laa t. Ver w ijd er da ar om r eg elm a ti g d e o v e rtollig e as. 1. O p e n d e de u r van he t t o e s tel. 2. G e b r u ik de s c h ud s tan g o m de over t o llige a s v ia h e t ro o s ter in de asla te late n valle n. 3. Ver w ijd er de a s la de met b eh ulp v an de bij g e le v e rd e kou de ha nd en lee g de aslad e; z ie d e volg en de t w e e f ig ur en. Haga su pregunta agui. Proporcione una descripcion clara y completa del problema y su pregunta. Cuantos mas detalles proporcione para su problema y pregunta, mas facil sera para otros propietarios de Dovre 2510 responder adecuadamente a su pregunta. Haz una pregunta Este manual pertenece a la categoria Chimeneas y ha sido calificado por 1 personas con un promedio de 5.2. Este manual esta disponible en los siguientes idiomas Espanol, Ingles, Holandes, Aleman, Francia, Italiano. Tiene alguna pregunta sobre Dovre 2510 o necesita ayuda. Haz tu pregunta agui Especificaciones de Dovre 2510 Nuestra base de datos contiene mas de 1 millon de manuales en PDF de mas de 10.000 marcas. Cada dia anadimos los ultimos manuales para que siempre encuentres el producto que buscas. Es muy sencillo simplemente escriba el nombre de la marca y el tipo de producto en la barra de busqueda y podra ver instantaneamente el manual de su eleccion en linea de forma gratuita. ManualPDF. es Si continua utilizando este sitio asumiremos que esta de acuerdo. Leer mas Estoy de acuerdo. Giv en klar og omfattende beskrivelse af problemet og dit sporgsmal.

Jo flere oplysninger du giver om dit problem og dit sporgsmal, jo lettere er det for andre Dovre 2510 ejere at svare korrekt på dit sporgsmål. Stil et sporgsmål Om Dovre 2510 Denne vejledning horer under kategorien Pejse og er blevet bedomt af 1 personer med et gennemsnit pa en 5.2. Denne manual er tilgngelig på folgende sprog Engelsk, Hollandsk, Tysk, Fransk, Spansk, Italiensk. Har du et sporgsmal om Dovre 2510 eller har du brug for hjlp Stil dit sporgsmal her Dovre 2510 specifikationer PDFmanualer.dk sikrer, at du hurtigt kan finde den manual, du leder efter. Vores database indeholder mere end 1 million PDFmanualer fra mere end 10.000 mrker. Hver dag tilfojer vi de nyeste manualer, sa du altid kan finde det produkt, du leder efter. Det er meget simpelt du skal bare indtaste mrke og produkttype i sogefeltet og du kan straks se den manual du onsker, online og gratis. PDFmanualer. dk Hvis du fortstter med at bruge dette site vil vi antage at du er indforstaet med det. Ls mere Ok. Zeptejte se zde. Poskytnete jasny a komplexni popis problemu a vasi otazku. Cim vice podrobnosti uvedete ke svemu problemu ve vasi otazce, tim snazsi bude pro ostatni majitele Dovre 2510S vasi otazku zodpovedet. Zeptejte se O Dovre 2510S Tato prirucka patri do kategorie Krby a byla ohodnocena 1 lidmi prumernym hodnocenim 7.7. Tato prirucka je k dispozici v nasledujicich jazycich Anglictina, Holandsky, Nemcina, Francouzstina, Spanelstina, Italstina. Mate dotaz ohledne Dovre 2510S nebo potrebujete pomoc. Zeptejte se zde Specifikace Dovre 2510S Nase databaze obsahuje vice nez 1 milion prirucek ve formatu PDF pro vice nez 10 000 znacek. Kazdy den pridavame nejnovejsi prirucky, takze vzdy najdete produkt, ktery hledate. Je to velmi jednoduche staci zadat znacku a typ produktu do vyhledavaciho pole a muzete si okamzite prohlednout prirucku vaseho vyberu online a zdarma. Pokud budete nadale prohlizet nase stranky predpokladame, ze s pouzitim cookies souhlasite. Vice Souhlasim. Delivery nationwide.

$\frac{https://www.interactivelearnings.com/forum/selenium-using-c/topic/18797/dc-superior-court-practice}{-manual}$

This model is ideal for an installation that would make it a central focal point or a room divider. The combustion chamber comfortably loads 50cm logs and there is an ash pan. Dovre stoves feature a glass aeration system that directs secondary combustion gases along the glass for a window that stays cleaner for longer and comply with new stricter emission standards. The unit comes with a top flue exit. Dovre is imported from Belgium, and comes with a 5 year limited warranty. Post your question here in this forum. Were committed to dealing with such abuse according to the laws in

your country of residence. When you submit a report, well investigate it and take the appropriate action. Well get back to you only if we require additional details or have more information to share. Note that email addresses and full names are not considered private information. Please mention this; Therefore, avoid filling in personal details. Please enter your email address. In fact, Dovres manufacturing expertise with premium grade cast iron is such that all cast parts on their stoves and fireplaces come with a 5 year guarantee. With expertly crafted wood burning and multifuel fires and stoves as well as highly convenient gas and electric models, there is a Dovre for every home. The units have solid cast iron fireboxes with controllable airwash class cleaning vent, primary vent control and riddling grate they also have variable electric fan assisted heat convection as standard. Dovre 2510 C classic square glass display Dovre 2510 R rustic rounding above glass Dovre 2510 CTD double sided classic square glass display Dovre 2510 RTD double sided rustic rounding above glass Download the specification sheet Download the user manual. Also included is an instruction manual. Once the fans are turned on they will start and stop by means of thermostat control. The convection chamber is made from 2mm mild steel. Logs up to 50cm in length can be used.

The riddling grate with open and close position ensures optimal combustion regardless of the fuel being used. Convection air can be channelled, through secondary ducts to adjacent rooms. Just be aware that this will decrease your convection in the primary area. Trim plate is an optional item. These units are effective and economical fuel users and produce heat by way of convection and radiation. There is something magical about the atmosphere of living flames and it will really turn your house into a home. These fireplaces are easy to operate and to clean. Turn your open brick fireplace into an effective and economic fuel user with the added advantage of an enormous heating capacity, by installing a Dovre insert. Some the inserts feature electrical fans that assist the convection to give a very quick and optimum heat distribution throughout the area. Heat is released into the surroundings long after the fire has gone out. Cast iron is resistant to strong thermal stress and retains its shape. The fireplace thus remains tight and has a very long service life. Use your fire optimally by installing a doublesided unit between two rooms. Logs up to 50cm can be used in most builtin units. With most builtin units, convection air can be ducted to other rooms with flexible ducting. Surrounds, mantelpieces and toolsets can be used creatively to add a beautiful Victorian or modern effect to your home interior. Rating Bad You need JavaScript enabled to view it. Click here to read our Privacy Policy. Valj en av produkterna for att enkelt hitta din manual. Hittar du inte produkten du letar efter. Ange da market och typen av produkt i sokfaltet for att hitta din manual. Bruksanvisni. ng Letar du efter en manual. Bruksanvisni.ng sakerstaller att du hittar manualen som du letar efter pa nolltid. Var databas innehaller mer an 1 miljon PDFmanualer fran over 10 000 marken. Varje dag lagger vi till de senaste manualerna sa att du alltid hittar produkten du letar efter.

Det ar valdigt enkelt ange bara market och typen av produkt i sokrutan for att omedelbart semanualen du onskar online helt gratis. Bruksanvisni. ng Om du fortsatter att anvanda den har webbplatsen kommer vi att anta att du godkanner detta. Las mer Ok. ForewordAnnex 1 Technical data sheet.19. Annex 2 Dimensions.20The Installation Manual and Operators Instructions must accompany this appliance. As well as instructions for installation and information about use, you will also findPlease read this booklet carefully before installation and before firing the unit. Save this booklet and pass to any subsequent user who can also profit by it. Your DOVRE purchase has made you the owner of a high quality product that sy mbolizes a new generation of energy saving and ecologically safe heaters, producingThrough the application of a revolutionary combustion concept DOVRE heaters achieve astonishingOur heaters are produced in accordance with ISO 9002, using state ofthe art produc tion means. In the unlikely event of a malfunction, you can always rely on DOVRE's aftersalesThis heater is designed to be installed in a living room and to be hermetically connected to a flue chimney. If the stove is professionally installed, connected to a wellfunctioning

chimney andPlease consult an expert when installing and connecting the heater. The manufacturer cannot be held liable for problems caused by faulty installation. The heating unit is best installed, commissioned, and checked by a competent installer who is aware of national and local legislation. The heater is designed to heat a room, which means that all surfaces, including the. Please do not place any curtains, clothes, laundry, furniture or other combustible is advised to make a fire in the stove with the highest possible intensity right after This may involve some It is necessary to maintain and regularly clean the stove and the chimney for the Please follow the cleaning instructions in the chapter concerned.

In case of a chimney fire, immediately close all air intake vents of the appliance and Broken glass should be replaced before using the heater again. The stove is specifically designed for burning certain kinds of fuels. In the technicalThe Dovre model is designed to provide a fireplace convection system without the The principle of operation is Warm air is produced from the inner cast iron surfaces of the Flexible piping This can be either in the same room as the appliance or in It is essential to ensure that the warm airThe cooler room air entering the lower level moves the warm air by convection. The fireplace should be hermetically connected to a wellfunctioning chimney, sufficiently enclosed to keep combustible materials floor and walls at a distance, and Please inform about national or local norms and regulations concerning this subject. Your distributor will give you the necessary advice. Please read the technical specifications under cover in this manual before installingThe chimney the flue has a double function. It draws air, that is necessary for good combustion, into the stove. It functions as an exhaust pipe for combustion gases via thermal or naturalThe heated air in the flue is lighter than the colder air outside the flue and consequently rises up, along with the combustion gases. Natural draught is caused by environmental phenomena, such as wind. It is prohibited to connect several heaters to one chimney for instance the centralPlease check which chimney is to be used for the stove you purchased and whether You should consider an expertsThe chimney should meet the following conditions. The flue should be made of fireproof material. Ceramic or stainless steel is recommended. The chimney should be airtight and thoroughly cleaned and should guarantee alt should run as vertically as possible.

Changes in direction or horizontal segments will disrupt the smoke flow and may cause soot to cumulate inside the The chimneys inside dime nsions must not be too large in order to prevent theFor recommended chimney dimensions, seeLarger dimensions can be used if the flueThe flues diameter should be the same throughout its whole length. Wider, or Especially if the flue runs through unhe ated rooms or outside the house, furtherMetal chimneys, or parts of the chimney outside heatedThe part of the chimney outside the roof should always be insulated. The chimney should be high enough at least four metres and should end in aThe rule of If the distance between the Depending on the presence of nearby buildings or trees, the chimney should be higher. The burning of wood, charcoal or gas involves oxygen consumption. It is of the utmost importance that the room in which the stove is installed should be sufficientlyInsufficient ventilation may disrupt the combustion process and cause the smokelf necessary, you can install a ventilation grille to provide a constant flow of fresh airThe DOVRE fireplace has been designed to produce most heat by means of convection. Heat is mainly transmitted through the back panel, the lateral panels, and the As this airFor optimal heating and leading the convection air, the airflow must not encounterIn case convection air is suppliedAt any rate, assure proper home air management and sufficient air supply into the Ensure not to use other airconsuming appliances, such as heaters, cooking hoods, The appliance shall be installed on floors with an adequate loadbearing capacity. Combustible material must be sufficiently protected. The floor under the fireplaceUnder the appliance. Under the appliance, any combustible material must be removed or specially The legs of the Floor round the appliance.

A floor made of combustible material must be properly shielded in the followingCombustible walls

behind, next to, or above the fireplace must be shielded with at Fireproof materials should be Within the radiation area of the fireplace. Assure a distance of at least 80 cm between the opening of the fireplace and combustible material. That distance may be reduced to 40 cm if the combustible material is sufficiently shielded and well ventilated. Outside the radiation area of the fireplace. Assure a distance of at least 5 cm between the mantleA wooden ornamental rafter must not be installed withinOutside the radiation area, No combustible material must be present within 50 cm from the convection outletPlease inspect the fireplace for damage caused during transport immediately afterDo not put the appliance into operation in the meantime. In order to avoid damaging the fireplace during installation and to make its handlingIt is possible to change the direction of the door ope ning. On each side you have already the system. You can remove the clapet and the tige by holding it upward and moving it a littleWhen you loose the bolt in the topplate you can remove the The decorative frames, 3 and 4 sides versions are fitted to the applaice after installation. Ensure that sufficient space is allowed to both sides of the recess. Assemble the different parts of the handle, I.e. a screw. M8x50, a wooden handle and a nut, as indicated on the sketch. For protection, the unit must always be connected to power. The appliance is supplied with a speed control to vary the running speed of the fans. This can be left trailing or fitted o the wall mounting supplied. The appliance is designed to be built into a new or existing chimney breast installation to provide space heating by radiant an convected heat. Build the new fire place around the appliance ensuring that no materials are builtNever build directly onto the appliance.

If flexible warm air ducts are to be used, install air grills at the outlet locations toWhere the fireplace backs onto another room or is in the corner of a room, backing Never use grills made from plastic or other combustible materials. Ensure that the weight of the main chimney or chimney flue liners is not directly supported by the appliance. Flue liners must be supported independently of the appliance. The recess should be formed using an appropriately designed raft lintel to support The minimum clearance between the It is recommended to fix insulating panels to the sides, back and top of the appliance. Never allow marble, granite or masonry to be in direct contact with the metal outerAlways use insulation. Prepare the opening ensuring that adequate support is provided for the chimney and Ensure that enough height is allowed to adequately If necessary, construct a raft lintel to If the recess is too wide, use insulated building blocks to reduce the width. Clean thouroughly the floor, wall and top of the recess. Stand the appliance in the recess and use a spirit level to ensure the unit is level and If an exiting masonry is installed, the appliance should be connected to the chimneyIt is important to ensure thatEnsure that the weight of the main chimney or chimney flue liners is not directly supported by the appliance. Flue liners must be supported independently of the appliance. When the appliance is installed in the right place, its connection with the chimney made airtight, and the masonry mantle completely mounted, all loose partsYour fireplace is now ready to be used. Depending on the materials used for mounting, it is recommended to wait for Attention never light a fire with the inner plates or refractory stones removed. Packaging materials should be disposed of in a responsible way and in accordance with governmental regulations.

CombustibleRefractoryOpening againstIsolation minExtra openingFireproff wallStainless steelInsulation ifCombustibleCanvection airConvection airConvection airFireproof floor. CombustibleExample of fireplace installation within combustible materialExtra opening forRefractory cement orExistant fireplace. Opening againstConvection airVentilationConvectionExample of installation in an existante fireplaceThe only suitable fuels for this stove are wood, brown coal briquettes and charcoalNo other fuels are allowed to be burnt, as they canDo not burn any tre ated wood either, such as scrap wood, dyed wood, impregnatedThe fumes of these, as of synthetic materials, old papers and household waste, are highly polluting for both your stove andTheyalso could cause chimney fires. Wood. Hard woods, such as oak, birch and fruittrees, are the ideal fuels for your stove. The wood must have dried for at least two years in a covered and wellventilatedDry wood should contain no more than twenty pe rcent moisture. Wet

logs are unsuitable for burning, as they do not produce enough heat and all ofMoreover, the burning of wet woodBrown coal briquettes. Brown coal briquettes burn in more or less the same way as wood does. You shouldCharcoal. There are several categories of anthracite coal. Some characteristics may be legallyThe ash content may range from 3 to 13%. For a good operation of your appliance, the use of anthracite "A" with a low ash content is recommended. A combustible with a high ash content has a lower net heatingIn order to c reate sufficient draught and to prevent smoke from being emitted intoA cold chimney can be heated up by lighting a ball of paper above the fire plate. Slightly open the door. It is important that the kindled fire should burn intensely. You can then throw largerWhen the fire has stabilized and isAlways keep the stove doors tightly closed. Never let the doors open when the fire isAdd extra fuel when necessary. Never add too much fuel.

It is best to fill the stoveAlways open the filling door slowly and for a short space of time. Before filling up, Check whether the coals are glowing enough just behind the log retainer, so that the added fuel will immediately Open stacking will make the logs burn very intensely, as the oxygen can easily reachThis method of stacking is applied when burning wood for aLow intensity fires cause tar and Tar and creosote are highly comopen stacking Therefore it is necessary for the fire to regularly burn very intensely, so that thin layers of tar and creosote immediately disappear. Low intensity fires also cause tar to deposit on the stove panes and doors. When it is not too cold outside it is better to let the stove burn intensely for just a You need a coalbasket for burning coal. After a few minutes, add some more coals until you can only see the glow of the previousWhen the fire basket or the castiron plate fins are redhot, you are heating too intensely. If your fireplace is equipped with an ashtray optional, itRelatively speaking, burning wood produces little ash and itStop fuelling the fire and let it burn out. You should let the fire burn out and keep an eye on it as long as it is still glowing. Attention! Mist and heavy fog will block the chimneys smoke outlet and may lead to smoke It is best not to use the fireplace under these weather conditions. It takes only little effort to keep your appliance in good condition. Regularly check whether the sealing cord still closes the doors tightly enough. Minor paint damage can be touched up with a can of spray paint. Your dealer canDuring the first use after repainting your unit might give off some slight odour. However, this will disappear quickly. The glass can be cleaned with a number of glass cleaning products available on the At the end of the heating season, seal off the chimney with a ball of paper. You can'f necessary, replace the sealing ropes and use fire cement to fill up possible leaks.

Remove the fireplate for better and more thorough cleaning. To remove the doors, disassemble the hinges as shown. You should have your chimney swept by an expert before the heating season begins. It is useful to check the chimney for soot during the heating season as well. Checking and maintaining the chimney is a statutory requirement. When all of the above advice is heeded, you will be able to fully e njoy your stove. Flue gas temperature Minimum draught Bois. Holz. Kolen. Charbon. Coal. KohlenBois. HolzBrowncoal. BraunkohlBruinkoolBrowncoal. BraunkohlFlue connection diametre. Nominal heat output. Model. Annex 1 technical data sheetBois. BraunkohlCharbon. KohlenDeclaration de conformite CE. EC Declaration of conformity. Konformitatserklarung CE. Notified body 1625. Wij. Nous. We. Wir. Dovre nv Nijverheidsstraat 18 B2381 Weelde Erklaren da das Produkt 2020; 2220; 2520;2210;2510; 2200; 2500 entsprichtIn het kader van een continue productverbetering, kunnen specificaties van het geleverde toestel afwijkenDans le cadre d'une amelioration constante des produits, les specifications du produit livre peuvent differerDue to continuous product improvement, specifications of the delivered product may differ from the content of this booklet, without further notice. Im Rahmen kontinuerlicher Produktverbesserung, konnen Specifikationen des geliefertes Produktes vonB2381 WeeldeFile Type Extension pdf. PDF Version 1.6. Linearized No. XMP Toolkit Adobe XMP Core 4.0c316 44.253921, Sun Oct 01 2006 170823. Create Date 20060609 133704Z. Creator LMeeus. Producer Acrobat PDFWriter 4.05 voor Windows NT. Document ID uuida2469a10db7711db90f8000d93b6703e. Instance ID uuidcc0f5323f25cd24bab73dd6a1f74f983. Has XFA No. Page Count 23. Author LMeeus.

https://www.becompta.be/emploi/dc-universe-manual-patch