



**File Name:** Dv448Agp Manual.pdf

**Size:** 1432 KB

**Type:** PDF, ePub, eBook

**Category:** Book

**Uploaded:** 11 May 2019, 23:15 PM

**Rating:** 4.6/5 from 708 votes.

**Status:** AVAILABLE

Last checked: 10 Minutes ago!

**In order to read or download Dv448Agp Manual ebook, you need to create a FREE account.**

[\*\*Download Now!\*\*](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

## Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dv448Agp Manual . To get started finding Dv448Agp Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



## Book Descriptions:

# Dv448Agp Manual

Are you sure to remove this product By continuing to browse or use this site, you are agreeing to our use of cookies. Please share your ZIP Code to find a nearby Best Buy to try out your next phone. Please share your ZIP Code to find a nearby Best Buy location Stainless Steel STS prevents rust and discoloration. Sensor Dry detects moisture levels and stops the cycle when a load is dry. Note If your phone is. If you're running the. Touch Smart Care on the washer or dryer, and then open. Sensor Dry cycles With Sensor Dry, you dont have. Ask a question or start a new topic to get help and advice from our loyal Samsung community. Or Text HELP to 62913 Please contact us via Live Chat for a faster response. Samsung pays for Premium Care during this period. Ask your question here. Provide a clear and comprehensive description of the issue and your question. The more detail you provide for your issue and question, the easier it will be for other Samsung DV448AGP owners to properly answer your question. Ask a question About the Samsung DV448AGP This manual comes under the category Washing Machines and has been rated by 1 people with an average of a 9.6. This manual is available in the following languages English, Spanish. Do you have a question about the Samsung DV448AGP or do you need help. Ask your question here Samsung DV448AGP specifications Scale deposits can be prevented by limiting washing at high temperatures and using the recommended amount of detergent per wash. ManualSearcher.com ensures that you will find the manual you are looking for in no time. Our database contains more than 1 million PDF manuals from more than 10,000 brands. Every day we add the latest manuals so that you will always find the product you are looking for. Its very simple just type the brand name and the type of product in the search bar and you can instantly view the manual of your choice online for free. ManualSearcher. <http://galenbio.com/images/upload/delete-printers-manually.xml>

- **dv448agp xaa manual, dv448agp manual.**

com If you continue to use this site we will assume that you are happy with it. Read more Ok. Please try again. Please try again. Please try again. Then you can start reading Kindle books on your smartphone, tablet, or computer no Kindle device required. Register a free business account To calculate the overall star rating and percentage breakdown by star, we don't use a simple average. Instead, our system considers things like how recent a review is and if the reviewer bought the item on Amazon. It also analyzes reviews to verify trustworthiness. All manuals on ManualsCat.com can be viewed completely free of charge. By using the Select a language button, you can choose the language of the manual you want to view. Thank you for purchasing this Samsung product. To receive more complete service, Ultra drying capabilities are at your fingertips. Now you can dry extralarge loads. Our This cycle sprays a small amount of water into the dryer drum after several minutes of This course allows you to sanitize garments by permeating high temperature heat deep into Use this course to keep your bedding and curtains clean. When selecting this cycle, 99.9% of certain bacteria is eliminated through high temperature Simply turn the Jog Dial to select one of the 11 automatic drying cycles, including normal, Precision drying has never been easier than with Samsung. Our cycles are designed with you in mind. All our dryers are designed to dry your clothes in Samsung dryers are super energy efficient. You can dry up to 3.01 pounds of laundry with Our dryers will fit just about anywhere and without a door conflict. The direction of our easy An optional 15" pedestal is available to raise the dryer for easier loading and unloading. It Samsung's Washer and Dryer can be stacked to maximize usable space. The Dryer legs need to be removed to stack the Washer and Dryer. You can purchase an You can install the exhaust vent in the following four 4 positions back, either side, bottom. NSF Protocol

Sanitization Performance of Residential Clothes Dryers Congratulations on your new Samsung Dryer. This manual contains valuable information. Please take the time to read it. It is your responsibility to use common sense, caution, and care when installing, using, and maintaining your dryer. Always contact your manufacturer about problems or conditions you do not understand. Do not store or use gasoline or other flammable vapors and liquids near this dryer. Do NOT attempt. Do NOT disassemble. Do NOT touch. Follow directions explicitly. Unplug the power plug from the wall socket. Make sure the machine is grounded to prevent electric shock. Call the service center for help. If flexible metal flexible venting materials are used, these conditions will obstruct the venting. **WARNING Risk of Fire** Installation and service must be performed by a qualified installer, service agency, or the gas supplier. Read all instructions before using the appliance. To reduce the risk of fire or explosion, do not use any material that has been in contact with a fire. There are many highly flammable items used in homes, such as acetone, denatured alcohol, and heated foam rubber materials. Do not allow children or pets to play on, in, or in front of the appliance. Close supervision is required. Before discarding or removing your dryer from service, remove the door to the drying drum. Do not reach into the appliance when the drum is moving. Do not install or store this appliance where it will be exposed to the weather. Do not tamper with controls. Do not repair, replace, or attempt to service any part of the appliance unless specifically recommended. Do not use fabric softeners or products to eliminate static unless recommended for dryer use. Clean the lint screen before or after each load. Keep the area around the exhaust opening and surrounding areas free from lint, dust, and debris. This appliance must be properly grounded. Never plug the power cord into a receptacle. Do not sit on top of the dryer.

Because of continuing product improvements, Samsung reserves the right to change details, see the Installation Instructions. Ensure pockets are free from small irregularly shaped hard objects, foreign material, etc. These objects could damage your dryer. Do not wash clothing with large buckles, buttons, or other heavy metal or solid things. Gas leaks may occur in your system, resulting in a dangerous situation. Gas leaks may not be detected by smell alone. Gas suppliers recommend you purchase and install a UL approved gas detector. Install and use in accordance with the manufacturer's instructions. Do not place items in your dryer that have been spotted or soaked with vegetable oil or residual oil on clothing can ignite spontaneously. The potential for spontaneous combustion exists. If this heat cannot escape, the items can become very hot. Piling, stacking, or storing these kinds of items may prevent heat from escaping. All washed and unwashed fabrics that contain vegetable oil or cooking oil can be a fire hazard. Always use the Cool Down cycle for these items to reduce their temperature. Never pile or stack these items when they are wet. Gas appliances can cause minor exposure to four of these substances, namely benzene, carbon monoxide, and nitrogen dioxide. Properly adjusted dryers will minimize incomplete combustion. Exposure to these substances can be harmful. If there is a service call performed as a result of poor setup, if you install the dryer you are installing, make sure you have everything necessary for proper installation. See Electrical Requirements. Adjustable legs. Control panel. Door. Do not use a flexible duct. Serious blockage can result if the flexible metal duct is bent too sharply. Do not use screws. The hood opening should point down. Do not exhaust under a house. Unplug the power cord before service. Note: If clothes are not getting dry, then check the lint screen. Recommended Use only for short run installation. If the new dryer is installed into an existing exhaust system you must make sure the static pressure in any exhaust system must not exceed 0.

83 inches of water column, or be less than 0.5 inches of water column. This can be measured with the dryer running with a manometer at the point where the exhaust duct enters the house. A no-heat setting should be used. The dryer tumbler should be vented to the outside. These instructions should be kept for future reference. This dryer is factory ready for rear exhaust. To exhaust out the dryer, adequate clearance as noted on the data plate must be maintained to ensure adequate airflow. See EXHAUST INFORMATION section. A louvered door with equivalent space clearance is required. When installing a dryer in a mobile home, provisions for anchoring the dryer to the floor must be made. Locate an area that has adequate fresh air. A minimum of 72 in x 465 cm of unobstructed space is

required. Call 1800SAMSUNG for information on purchasing the Floor Anchoring Kit as an accessory. All mobile home installations must be exhausted to the outside with the exhaust duct termination securely. The exhaust duct may not terminate underneath the mobile home. See Exhausting section for more information. In the United States In Canada Outside the U.S. and Canada. The dryer must be exhausted to the outside to reduce the risk of fire when installed in an Use only a metal exhaust duct that is nonflammable to ensure containment of exhaust air, If you plan to use your dryer with LP Gas dryers installed in residential garages must be raised 18 inches 46 cm above the floor. Your dryer must be disconnected from the gas supply pipe system during any pressure testing of the DO NOT reuse old flexible metal gas lines. Flexible gas lines must be design certified by the American Gas. Association CGA in Canada. There is no constant burning pilot. Commonwealth of Massachusetts installation instructions. Your dryer must be installed by a licensed plumber or gas fitter.

A "T" handle manual gas valve If a flexible gas connector is used to install Check with a qualified electrician or serviceman if you are in doubt as to whether your dryer is It is your responsibility to provide In the event of malfunction or breakdown, the ground will reduce the risk of Gas models. Your dryer has a cord with an equipment grounding conductor and a grounding plug. The plug must be plugged into an appropriate outlet that is properly installed and grounded in Your dryer has a cord with an equipment grounding conductor and a grounding plug, sold The plug must be plugged into an appropriate outlet that is properly installed and grounded in If a power cord is not used and the electric dryer is to be permanently wired, the dryer must An individual branch or separate circuit serving only your dryer is recommended. Some require. The electric service requirements can be found A 30 ampere fuse or circuit breaker on both sides of The power cord electric supply wiring The power cord should be It is not permissible to convert a dryer in Canada to 208 volts. The dryer must be connected to the cold water faucet using the new inlet hoses. Do not use old Do not overtighten, as it may damage the coupling. Screw on coupling by Do not overtighten, as it may damage the coupling. Method 2. The dryer must be connected to the cold water faucet using the new inlet hoses. Do not use old Screw on coupling by hand until it is seated on the faucet. Do not overtighten, as it may damage the coupling. Screw on coupling by hand until it is seated on connector. Do not overtighten, as it may damage the coupling. Screw on coupling by hand Do not overtighten, as it may damage the coupling. Short hose Long hose Read and follow the instructions provided with any tools listed here. Tools and Parts. Pliers Cutting knife Pipe wrench gas only Nut drivers. Level Phillips Screwdriver Duct tape Wrench. For proper installation, we recommend that you hire a professional.

To install Consider installing the dryer and washer side Lay two of the carton cushion tops on the floor. Tip your dryer on its side so it will lay across both To set the dryer to the same height as the washer, fully retract the Adjust the leveling feet only as much as necessary to level the dryer. Extending the leveling feet more than necessary can cause the dryer Level. Leveling feet. Retract fully Then loosen Install the ductwork from your dryer DO NOT use sheet metal screws when assembling ducting. These joints should be taped. Never use plastic flexible exhaust material. Tip for tight installations install a section of exhaust system to your dryer before putting it in place. Use duct tape to secure this section to your dryer, but do not cover ventilation slots at the back of the BEFORE OPERATING OR TESTING, follow the grounding instructions in the Grounding section. A 4 WIRE SYSTEM CONNECTION is required for new or remodeled construction, mobile If the 4 wire system is used, Refer to the Remove the terminal block cover plate. Insert the power cord with a UL listed strain relief through the hole provided in the cabinet near the A strain relief must be used. Do not loosen the nuts already installed on the terminal block. Be sure they are tight. Remove the pipe thread protective cap. Pipe joint compound must be resistant to the action of any liquefied petroleum gas. Connect the gas supply to your dryer. Securely tighten the gas line fitting over threads. Turn on the gas supply. Check all gas connections for leaks using a soap solution. If bubbles

appear, tighten the connections and recheck. DO NOT use an open flame to check for gas leaks. Tighten screws. Secure the cover with a hold-down screw. If converting from a 4-wire electrical system to a 3-wire, the ground strap must be tightened. Tighten screws. Secure the cover with a hold-down screw. The burner may not ignite initially due to air in the gas line.

Allowing your dryer to operate on a heat. If the gas does not ignite within 5 minutes, turn your dryer off and wait 5 minutes. In order to confirm gas ignition, tape all joints, including at Never use lint-trapping screws. Be sure the vent flap opens and closes freely. Inspect and clean the exhaust system annually. Don't let a poor exhaust system slow drying by. To select a cycle, rotate the Cycle Selector dial to the desired cycle. The indicator light by the cycle name will illuminate. The Normal, Heavy Duty, Towels, Perm Press and Delicates cycles are Sensor Dry cycles. Sensor Dry automatically senses the moisture in the load and shuts the dryer off. The cycle minimizes wrinkling by providing a longer Sanitize. This course allows you to sanitize garments by permeating high. Use this course to. Turn the Cycle Selector dial to Time Dry, then press the Adjust Time up arrow to. Press the arrow repeatedly to scroll through the time settings. Quick Dry Provides a 30 minutes drying cycle. Overloading the dryer may not yield the same results. Instructions. Tips. Digital Graphic. Display. The display window shows the estimated time remaining in the cycle after the. The estimated time remaining may fluctuate as the. The Drying light will illuminate and remain lit until the cycle is complete. When your dryer is in the cooldown phase, the Cooling light will illuminate. When your dryer is in the wrinkle prevent phase, the Wrinkle Prevent light will. When the cycle is complete, "END" will appear in the display panel until the dryer. Pause button is pressed. Dry Level. Selection Button. To select the dry level in the Normal, Heavy Duty, or other Sensor Dry cycles, an indicator light will illuminate next to the desired. Press the button repeatedly to scroll through the settings. Larger or bulkier loads. The Less Dry setting is best suited for lightweight fabrics or for leaving some. Damp Dry is designed to partially. Temp Selection. Button. To select the correct temperature for the load, press the Temp button.

An indicator. Press the button repeatedly to. Tumble Dry Medium. Time Selection. When using Manual Dry cycles, time can be adjusted by pressing the time. During the Sensory Dry cycle, the time light indicator is off because exact drying. Signal Selection. When the cycle is complete, a chime will sound. When the Wrinkle Prevent option is selected, the chime will sound intermittently. Adjust the volume of the chime or turn it off by pressing the Signal button. Press the button repeatedly to scroll through the choices. Select Cycle. Option. To add or subtract time from the cycle, press the Adjust Time arrow pad up or. Wrinkle Prevent. Wrinkle Prevent provides approximately 90 minutes of. Press the Wrinkle Prevent button to activate this feature. The indicator light above the pad will illuminate when Wrinkle Prevent is selected. The load is dry, and can be removed at any time during the Wrinkle Prevent cycle. Temperature will be set only. Mixed Load Bell. This is an alarm that notifies the user of the time when the. This function can only be selected in the Sensor Dry course, and the dry level can. Press to pause and restart programs. Power button. Press once to turn your dryer on, press again to turn it off. If your dryer is left. If you want to set or release the Child Lock, press both the Time and Signal buttons. How to Set. When other buttons, except for the Power button, do not respond, check the Child Lock. Instructions. Tips. If you want to set or release the Drum Light, press both the Dry Level and Temp. buttons. It can be set while your dryer is not only running but also when it is stopped. If you do not turn the Drum Light off 4 minutes after turning it on, the Drum Light is. Press and hold the Rack Dry and Wrinkle Prevent buttons for 3 seconds until the display changes. Then. Once set, the selected language will remain in memory, even if the dryer is turned off or unplugged. By pushing the My Cycle button, you activate the settings used during the previous My Cycle mode.

If My Cycle mode is activated, the My Cycle indicator will be lit. You can select all options in My Cycle mode as follows. Each cycle has certain default options that are automatically set. To see these

default options, go to page F3. The cycle and You can change the My Cycle settings by repeating the same process above. The last used setting will be displayed the next time you choose My Cycle. Select the time according to the moisture and weight of the items. Start dryer. It may be necessary to reset the timer if a longer drying time is needed. Heat Extra Low. Stuffed toys Heat Extra Low. Stuffed toys Air Fluff. Foam rubber pillows Air Fluff. Sneakers Air Fluff. Drying foam rubber, plastic, or rubber on a heat setting may cause damage to the items Instructions. Tips This improves the tumbling action and drying efficiency. The time may fluctuate to better indicate drying time remaining in the cycle. Do not use abrasive substances. Do not spray cleaners directly on the panel. The control panel finish may be damaged by some laundry pretreatment soil and stain remover products. Apply such products away from your dryer and wipe up any spills or overspray immediately. Tumble old towels or rags to remove any excess stain or cleaning substance. Once these steps are followed, stains may still be visible, but should not transfer to subsequent loads. Remove the cleaner residue and dry with a clean cloth. Do not use abrasive substances. Protect the surface from sharp objects. Do not place any heavy or sharp objects or a detergent box on the dryer. Keep them on the purchased This may scratch or damage the top cover of the dryer. Since the entire dryer has a high gloss finish, the surface can be scratched or damaged. Therefore, avoid scratching or damaging the surface when using the dryer. The outside exhaust hood should be cleaned more frequently to ensure proper operation. High temperature. Foam Rubber rug backs, Use the Air Fluff cycle no heat. Use the Air Fluff cycle.

Plastics shower curtains, Low temperature settings depending on the care label instructions. Ducting should be inspected Add a few towels. Remove promptly. Sort heavy items from lightweight items for best drying results. This is normal as Remove some items and restart the dryer. With some loads Garments still wrinkled after. Wrinkle Care. Odors remain in clothing Water drips from nozzle The dripping water will stop after a short Sprayed water is not visible The Clothing care labels include symbols for The use of symbols ensures Wash Cycle Special Instructions. Warning Symbols for. Laundering. Wrinkle Control. Drip Dry Do Not Wring. Hand Wash Heat Setting Do Not Tumble Dry. No Steam added to Hot Medium Do Not Iron. Warm Low Dry clean. Cold Any Heat Dry Clean. Any Bleach when Iron Dry or Steam. Temperatures. Only Non Chlorine Bleach when needed. High Drip Dry. Tumble Dry Cycle Medium Dry Flat. Normal Low. Wrinkle Control If you decide to dispose of this appliance, please Cut off the power cord so that the appliance cannot be connected. A. Height 39" 99.1. C. Depth with WEIGHT 55.16kg Default Drying Cooling. Wrinkle Temp Sensor dry Time Time Time. Sensor Dry. Normal. High Normal dry 44 min 39 min 5 min 90 min. Heavy Duty. High Normal dry 60 min 55 min 5 min 90 min. Towels. High Normal dry 52 min 47 min 5 min 90 min. Perm Press. Medium Normal dry 34 min 24 min 10 min 90 min. Delicates. Low Normal dry 29 min 24 min 5 min 90 min. Sanitize. High Very dry 60 min 55 min 5 min 90 min. Manual Dry. Time Dry High 40 min 35 min 5 min 90 min. Air Fluff No change 20 min 20 min 90 min. Quick Dry High 30 min 25 min 5 min 90 min. Steam. Cycles. Refresh. High Wrinkle Care. Medium SAMSUNG against manufacturing defects in materials and workmanship for a limited warranty period of. One 1 Year All Parts and Labor. Two 2 Years Control Board Parts.

This limited warranty begins on the original date of purchase, and is valid only on products purchased and To receive warranty service, the purchaser must contact SAMSUNG for problem determination and service Warranty service can only be performed by a SAMSUNG authorized service center. The original dated bill of sale must be presented upon request as proof of purchase to SAMSUNG or. SAMSUNG's authorized service center. SAMSUNG will provide inhome service during the warranty period at no charge, subject to availability Inhome service is not available in all areas. To receive inhome service, product must be unobstructed and accessible to the service agent. If service is not available, SAMSUNG may elect to provide transportation of the product to and from an SAMSUNG will repair, replace, or refund this product at our option and at no charge as stipulated herein, All replaced parts and products become the property of SAMSUNG and must be returned to

SAMSUNG. Replacement parts and products assume the remaining original warranty, or ninety 90 days, whichever isThis limited warranty covers manufacturing defects in materials and workmanship encountered in normal,This limited warranty does not cover problems resulting from incorrect electric current, voltage or supply,SAMSUNG does not warrant uninterrupted or errorfree operation of the product.To obtain warranty service, please contact SAMSUNG atArlington, NJ 07856U.S.A 1800SAMSUNG7267864 www.samsung.com. MEXICO 01800SAMSUNG7267864 www.samsung.comPerhaps the users of ManualsCat.com can help you answer your question. By filling in the form below, your question will appear below the manual of the Samsung DV448AGP. Please make sure that you describe your difficulty with the Samsung DV448AGP as precisely as you can. The more precies your question is, the higher the chances of quickly receiving an answer from another user. You will automatically be sent an email to inform you when someone has reacted to your question.

Refer to Service Manual DV220, DV221, DV210, DV350, DV339, DV338, DV331, DV330, DV448, DV438, DV428, DV419, DV410, DV409, DV407 for detailed installation, operating, testing, troubleshooting, and disassembly instructions. Page 2 ALIGNMENT AND ADJUSTMENTS WARNING To avoid risk of electrical shock, personal injury or death; disconnect power to dryer before servicing, unless testing requires power. ERROR ITEMS AND DIAGNOSTIC CODES An occurrence of an Error will make a sound of error melody for 5sec and con tinuously show one of the Error Displays from the following errors. LED Error Display LCD Trigger Action Taken tS to tE Check for The Termistor resistance is very Clogged lint screen.Page 3 ALIGNMENT AND ADJUSTMENTS WARNING To avoid risk of electrical shock, personal injury or death; disconnect power to dryer before servicing, unless testing requires power. Temperature Display Modein Celsius Definition of Temperature Display Mode With power on, Press Sinal and Wrinkle Prevent keys simultaneously for 3 seconds. This action will put the dryer into Touch Sensor Mode Under "Touch Sensor Mode", Press Time and Wrinkle Prevent Keys at the same time. Page 5 ALIGNMENT AND ADJUSTMENTS WARNING To avoid risk of electrical shock, personal injury or death; disconnect power to dryer before servicing, unless testing requires power. TROUBLE DIAGNOSIS As the micom dry machine is configured of the complicate structure, there might be the service call. Below information is prepared for exact trouble diagnosis and suitable repair guide. Caution for the Repair and Replacement Please follow below instruction for the trouble diagnosis and parts replacement. Page 6 TROUBLE SHOOTING WARNING To avoid risk of electrical shock, personal injury or death; disconnect power to dryer before servicing, unless testing requires power. Idler tension spring too weak or stretched. Low voltage present. Blower impeller blocked in blower housing.

Page 7 TROUBLE SHOOTING WARNING To avoid risk of electrical shock, personal injury or death; disconnect power to dryer before servicing, unless testing requires power. Page 8 TROUBLE SHOOTING WARNING To avoid risk of electrical shock, personal injury or death; disconnect power to dryer before servicing, unless testing requires power. COMPONENT TESTING PROCEDURES Component Electrical Testing with ohmmeter. GAS MODEL Radiant Sensor10RS Resistance value Page 10 TROUBLE SHOOTING WARNING To avoid risk of electrical shock, personal injury or death; disconnect power to dryer before servicing, unless testing requires power. Please use the box above to search for any other information.The heater coil failed, we continued to run the dryer with no heat. Mine Has A Blowout Near The Seam.What can I p. This is due to engine percolation. That means that your engine will actually hea. Please use the box above to search for any other information.Gas and Electric Dryer Thank you for purchasing this Samsung product. Easy Reversible Door. Our. Follow directions explicity. This manual contains valuable information on your new Samsung Dryer. Hazards or unsafe practices that may result in this or any other appliance. Follow the information in severe personal injury.to prevent electric shock. It is grounded to use common sense, caution, and care when installing, maintaining, or operating your dryer.Congratulations on the installation, use, and care of your appliance.Do not use fabric softeners or products to eliminate

static unless recommended for dryer use any appliance. Read all occupants. **SAVE THESE INSTRUCTIONS.** Before discarding or removing your dryer from service, remove the door to the drying compartment to prevent children or animals from lint, dust, and dirt. Do not. Do not wash clothing with your dryer. Never pile or stack these items may not be cleaned periodically by smell alone. For complete details, see the Installation Instructions.

The potential for grounding this heat cannot escape, the items can create a fire hazard. Gas leaks may contain significant amounts of continuing product improvements, Samsung reserves the right. **GAS LINES** if a gas dryer must be rigid metal or flexible stiffwalled metal exhaust ducting. 01 Installing your dryer Door. Adjustable legs. Long inlet hose. Rubber washers Make sure you are responsible. If. Never use nonmetallic flexible duct. Keep the exhaust duct as straight and. Check frequently to reduce condensation and lint buildup. A no airflow obstruction. Its important to ensure adequate air for future reference. Call 1800 SAMSUNG for more information. The dryer must be exhausted to the outside with the appliance by the manufacturer and that comply with metal. **DO NOT** reuse old flexible metal gas lines. Flexible gas lines must. In the event of malfunction or breakdown, the ground will reduce the risk of electric shock. Check with your dryer if it doesnt fit the outlet, have a proper outlet installed by a qualified electrician. Do not modify the plug provided with a. Installing your dryer Check that the water faucets are on fill valve connector. 6. Fasten the. Tools and Parts Move your dryer on the floor. To minimize vibration, noise, and unwanted movement, the floor must Level be. Insert the power cord with a UL listed strain relief through neutral. Install the ductwork from your dryer, but do not permit grounding through the hole provided in the Grounding section. Use duct tape to secure this section to the. the terminal block. **DO NOT** use plastic flexible exhaust material. Never use sheet metal screws when assembling ducting. U.S. Remove the terminal block cover. **DO NOT** use an open flame to check for leaks using a soap solution. An additional fitting is required to the neutral conductor.. Allowing crushed or clogged ducts and vent. 1 2 Never use linttrapping screws. Make sure your dryer is installed properly so it exhausts air easily.